

526236

Rec'd PCT/PTO 28 FEB 2005

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
1 April 2004 (01.04.2004)

PCT

(10) International Publication Number  
WO 2004/027161 A1

(51) International Patent Classification<sup>7</sup>: E02D 29/02,  
17/20

Francesco [IT/IT]; Via Gandolfi 58, I-40050 Ca' de' Fabbri (IT).

(21) International Application Number:  
PCT/IB2003/004139

(74) Agents: PROVVISIONATO, Paolo et al.; Provvisionato & Co S.r.l., Piazza di Porta Mascarella, 7, I-40126 Bologna (IT).

(22) International Filing Date:  
18 September 2003 (18.09.2003)

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(25) Filing Language: Italian

(26) Publication Language: English

(30) Priority Data:  
BO2002A000596  
19 September 2002 (19.09.2002) IT


(71) Applicant (*for all designated States except US*): OFFICINE MACCAFERRI S.P.A. [IT/IT]; Via Agresti 6, I-40123 Bologna (IT).

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(72) Inventor; and  
(75) Inventor/Applicant (*for US only*): FERRAILOLO,

[Continued on next page]

(54) Title: IMPROVED ELEMENT FOR FORMING GROUND COVERING, RESTRAINING AND REINFORCING STRUCTURES



(57) Abstract: An improved element for forming ground covenring, restraining and reinforcing structures, comprising a lower wall (L), an upper wall (U) and a front wall (F) connected in an articulated manner, at one of ots end edges (3, 4) at least, to an edge of the lower wall (L) or the upper wall (U).

WO 2004/027161 A1

**Declarations under Rule 4.17:**

- as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)
- as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii)) for the following designation US
- of inventorship (Rule 4.17(iv)) for US only

**Published:**

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

IMPROVED ELEMENT FOR FORMING GROUND COVERING, RESTRAINING AND  
REINFORCING STRUCTURES

The present invention relates to the sector of ground covering, restraining and reinforcing structures, for instance for the stabilisation of slopes, embankments and the like.

The applicants have in the past developed various structures of the type described above which have proved particularly appropriate and effective. For instance, document EP 1012406 in the name of the applicants discloses a structure formed by a framework of wire netting of the double twist type, folded to form a structure with a base wall, a front wall and a rear wall. The front wall of wire netting is reinforced with a further panel of electrically welded wire netting. A geosynthetic layer on the front wall makes it possible to provide "green" walls and can be used for the growth of vegetation which helps to stabilise the slope.

Although the structures described above have demonstrated that they can effectively perform their task of stabilisation, their construction on site requires skilled workers and specific equipment. When stabilising steep slopes, for instance, a scaffolding has to be erected at the front of the works in order to enable access to the structure from the front wall side in order to carry out the manual folding of the wire netting and thus produce the upper wall section. During this folding, moreover, the metal structure of the netting has to be deformed at the fold line, making site installation operations laborious and in some cases not very precise.

The object of the present invention is to resolve the above-mentioned problems by means of an improved element for forming ground covering, restraining and reinforcing

structures which can be correctly installed on site in a simple manner, possibly by relatively unskilled workers, and which does not, moreover, require the use of specific equipment or the erection of scaffolding at the front of the works.

A further object of the invention is to provide an improved element which is simple and economic to produce, can be readily transported from factory to site and also has a strength and a reliability at least equivalent to those of the elements of known type.

In order to achieve the above-described objects, the present invention relates to an improved element having the characteristic features set out in the following claims.

Further characteristic features and advantages are set out in the following detailed description of a preferred embodiment, given purely by way of non-limiting example, and made with reference to the accompanying drawings, in which:

- Fig. 1 is a perspective view of an improved element of the present invention, in a ready-for-use configuration;
- Figs. 2 to 6 show the successive stages of use of the improved element of Fig.1;
- Fig. 6a is a variant of the end-use configuration of Fig. 6;
- Fig. 7 is a section through a restraining wall or reinforced slope comprising superimposed layers formed by a plurality of elements of Fig. 1.

With reference to Fig. 1, an element 1 for forming ground covering, restraining and reinforcing structures of the present invention comprises a front wall F, a lower wall L and an upper wall U. The front wall F comprises a front panel 2 with two opposite edges 3, 4 connected in an articulated manner to a lower panel 5 of the lower wall L and an upper

panel 6 of the upper wall U respectively. The panels are preferably of wire netting and the front panel 2 can in particular be made from electrically welded wire netting, for instance of the square mesh type, while the lower and upper panels 5 and 6 can be made from wire netting preferably, but not exclusively, of the double twist and hexagonal mesh type. The articulated connections between the panels are preferably made at the factory by means of mechanised metal staples, metal ties or other known connection means.

A covering layer 7 of geosynthetic material or bio-matting may be secured where appropriate to the front panel 2 and may be extended to cover all or part of the lower and upper panels 5 and 6 as well. Brackets 8, preferably but not exclusively of triangular shape, are also connected to the front panel 2. The brackets 8 may also be in the form of bars secured or hooked to the front panel 2 and/or the lower panel 5. In the case of the triangular brackets 8 shown in the drawings, only the front side 9 of each bracket is connected in an articulated manner to the front panel 2 so that the brackets 8 may be folded against the front panel 2, as shown by the dot-dash line 10 in Fig. 1, for more convenient transportation of the element 1 in a flat form from the factory to the site.

The preferred configuration for transportation of the element 1 is shown in Fig. 2, in which the front panel 2 and the upper panel 6 are folded onto the lower panel 5 whose dimensions are normally larger. It will be appreciated that, depending on the particular dimensions of the netting panels which form the element 1 and/or the convenience of packaging of the elements 1, as well as the type and dimensions of the vehicles used to transport these elements, that the panels may be folded in an alternative way, for instance in zigzag form, in which the upper panel 6 is placed on the front panel 3 as shown by the dashed arrow 11 of Fig. 2.

After placing the element 1, and in particular the lower panel 5, on the section of ground to be reinforced, the front panel 2 is raised, as shown in Fig. 3, until it reaches a position inclined to a greater or lesser extent with respect to the lower panel 5. The front panel is held in position by the brackets 8 which are oriented so that the ends of a rear side 12 thereof bear on the lower panel 5 and the front panel 2 respectively. It will be appreciated that this object could be achieved by alternative brackets in the form of simple bars as mentioned above. The upper panel 6 may be held manually in the raised position shown in Fig. 3 or may be placed on the front surface of the front wall 2 by causing it to tilt in the direction of the dashed arrow 13. Obviously, when the element 1 is to be transported to the site in the zigzag folded configuration mentioned above, the upper panel 5 would already be in the above-mentioned position folded on the front surface of the front panel 2.

The ground reinforcing operations continue with the provision of a layer of earth, preferably topsoil, at the rear of the front panel 2, as shown in Fig. 4. The layer of earth 14 is preferably arranged so that it has, in cross-section with respect to the layers of panels of the element 1, a substantially triangular profile. If the upper panel 6 is not too high, and in particular substantially corresponds to or is lower than the height of the front panel 2, is it possible to tilt this upper panel 6 in the direction of the dashed arrow 15 of Fig. 4 until it is alongside the rear flank of the layer of earth 14, as shown by reference numeral 16 in Figs. 5 to 7. As an alternative, it is possible to place the upper panel 6 on a further layer of earth 17, preferably a structural embankment, which is placed alongside, as shown in Fig. 6, the first layer of earth 14 to complete one of the plurality of layers 18 of the reinforcing works shown overall in Fig. 7 and formed by a sequence of superimposed elements 1. In this latter case, the final configuration of the

element 1 bears the conventional "C"-shaped configuration, in which the lower and upper panels 5 and 6 are substantially parallel.

Many variants are possible with respect to the preferred embodiment described above. For instance, the front, lower and/or upper walls F, L and U may be made from a plurality of wire netting panels connected to one another rigidly or in an articulated manner. For instance, the upper wall U could be divided into two portions comprising at least two wire netting panels 6a, 6b connected together and articulated along a common edge 20, shown diagrammatically in dot-dash lines in Fig. 6a, substantially parallel to the edges 3, 4 of the front panel 2. This makes it possible to provide the layer of earth 14 with a configuration, in cross-section with respect to the layers of panels of the element 1, with a substantially trapezoidal profile at whose apex the panel 6a is placed, while the panel 6b is placed on the inclined side opposite to the front wall F so that it can then be incorporated in the earth 17 provided subsequently. Obviously, in the case in which the upper wall U is placed on the earth in a position substantially parallel to the lower wall L, the configuration of the layer of earth 14 may be triangular or trapezoidal.

The embodiments and structural details of the invention may obviously be widely varied from those described and illustrated, without prejudice to the principle of the invention and without thereby departing from the scope of the present invention.

## 6

CLAIMS

1. An improved element for forming ground covering, restraining and reinforcing structures, with a front wall (F) comprising at least one panel (2) of electrically welded wire netting, a lower wall (L) and an upper wall (U) each comprising at least one panel (5, 6, 6a, 6b) of double-twist hexagonal-mesh wire netting, the front wall (F) being connected in an articulated manner at one of its end edges (3, 4) at least, to an edge of the lower wall (L) or the upper wall (U).
2. An improved element as claimed in claim 1, characterised in that the front wall (F) is connected in an articulated manner at two of its opposite end edges (3, 4) to an edge of the lower wall (L) and an edge of the upper wall (U) respectively.
3. An improved element as claimed in claim 1 or 2, characterised in that the upper wall (U) has a height substantially corresponding to or lower than the height of the front wall (F).
4. An improved element as claimed in one of claims 1 to 3, characterised in that it comprises bracket means (8) adapted to support, in use, the front wall (F) in an inclined configuration with respect to the lower wall (L).
5. An improved element as claimed in claim 4, characterised in that the bracket means comprise at least one triangular bracket (8) with a side secured in an articulated manner to the front wall (F).
6. An improved element as claimed in any one of the preceding claims, characterised in that a layer of geosynthetic material or bio-matting is secured to the front wall.

BEST AVAILABLE COPY



7. An improved element as claimed in any one of the preceding claims, characterised in that the articulated connection of the front wall (F) to the lower wall (L) and/or the upper wall (U) is factory-made, the element being stowed and/or transported to the place of use in a flat configuration in which the front wall (F) is placed on the lower wall (L) and/or the upper wall (U).

8. An improved element as claimed in claim 7, characterised in that the front wall (F) is connected in an articulated manner to both the lower wall (L) and the upper wall (U), the element (1) being stowed and/or transported to the place of use in a flat configuration in which the front wall (F) and the upper wall (U) are both placed on the lower wall (L).

9. An improved element as claimed in claim 7, characterised in that the front wall (F) is connected in an articulated manner to both the lower wall (L) and the upper wall (U), the element (1) being stowed and/or transported to the place of use in a flat configuration in which the front wall (F), the upper wall (U) and the lower wall (L) are folded and placed at least partially on top of one another in a zigzag configuration.

10. An improved element as claimed in any one of the preceding claims, characterised in that the upper wall (U) comprises at least two panels (6a, 6b) connected in an articulated manner along a common edge (20) substantially parallel to the edges of the front wall (F).

BEST AVAILABLE COPY

## INTERNATIONAL SEARCH REPORT

 Invention No.  
 PCT/IB 03/04139

 A. CLASSIFICATION OF SUBJECT MATTER  
 IPC 7 E02D29/02 E02D17/20

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

 Minimum documentation searched (classification system followed by classification symbols)  
 IPC 7 E02D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

| Category * | Citation of document, with indication, where appropriate, of the relevant passages  | Relevant to claim No. |
|------------|---|-----------------------|
| X          | WO 00 31350 A (SYTEC BAUSYSTEME AG ; VON KAENEL HANS RUDOLF (CH))<br>2 June 2000 (2000-06-02)<br>page 3, paragraph 1 -page 6, paragraph 3;<br>figures 1,3,4                   | 1-4,6-11              |
| X          | WO 96 17134 A (PHI GROUP LIMITED ; PRICE IAN RICHARD (GB); BIGG KENNETH CHARLES (G))<br>6 June 1996 (1996-06-06)<br>page 2, paragraph 4 -page 17, paragraph 2;<br>figures 1,5 | 1-3,6-11              |
| X          | WO 96 33314 A (FJERBY A S ; AANDERAA JENS ODDVAR (NO)) 24 October 1996 (1996-10-24)<br>the whole document   | 1,3-11                |
|            | -/--  |                       |

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

## \* Special categories of cited documents :

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the international filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

- \*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- \*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- \*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- \* & \* document member of the same patent family

Date of the actual completion of the international search

4 February 2004

Date of mailing of the international search report

12/02/2004

Name and mailing address of the ISA

 European Patent Office, P.B. 5818 Patentlaan 2  
 NL - 2280 HV Rijswijk  
 Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
 Fax: (+31-70) 340-3016

Authorized officer

Geiger, H

## INTERNATIONAL SEARCH REPORT

Int. Application No.

PCT/IB 03/04139

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

| Category * | Citation of document, with indication, where appropriate, of the relevant passages   | Relevant to claim No. |
|------------|--|-----------------------|
| X          | DE 44 09 538 A (ROTHFUSS THOMAS ; KOHL<br>ALFRED (DE)) 2 February 1995 (1995-02-02)<br>column 1, line 34 -column 6, line 33;<br>figure 1 | 1, 3-11               |
| A          | EP 0 197 000 A (RUEGGER RUDOLF ; LANDOLT<br>FRITZ AG (CH)) 8 October 1986 (1986-10-08)<br>the whole document                             | 1-11                  |

## INTERNATIONAL SEARCH REPORT

Int. Application No  
PCT/IB 03/04139

| Patent document<br>cited in search report |   | Publication<br>date |    | Patent family<br>member(s) | Publication<br>date |
|---|---|---------------------|----|----------------------------|---------------------|
| WO 0031350                                | A | 02-06-2000          | AT | 224480 T                   | 15-10-2002          |
|   |   |                     | AU | 6457799 A                  | 13-06-2000          |
|   |   |                     | WO | 0031350 A1                 | 02-06-2000          |
|   |   |                     | DE | 59902793 D1                | 24-10-2002          |
|   |   |                     | EP | 1131498 A1                 | 12-09-2001          |
|   |   |                     | HU | 0104173 A2                 | 28-03-2002          |
| WO 9617134                                | A | 06-06-1996          | AT | 176289 T                   | 15-02-1999          |
|   |   |                     | AU | 688156 B2                  | 05-03-1998          |
|   |   |                     | AU | 3875595 A                  | 19-06-1996          |
|   |   |                     | DE | 69507642 D1                | 11-03-1999          |
|   |   |                     | DE | 69507642 T2                | 08-07-1999          |
|   |   |                     | EP | 0796375 A1                 | 24-09-1997          |
|   |   |                     | ES | 2128101 T3                 | 01-05-1999          |
|   |   |                     | WO | 9617134 A1                 | 06-06-1996          |
|   |   |                     | NZ | 295419 A                   | 28-07-1998          |
| WO 9633314                                | A | 24-10-1996          | NO | 951465 A                   | 21-10-1996          |
|   |   |                     | AU | 5410296 A                  | 07-11-1996          |
|   |   |                     | WO | 9633314 A1                 | 24-10-1996          |
| DE 4409538                                | A | 02-02-1995          | DE | 4409538 A1                 | 02-02-1995          |
|   |   |                     | DE | 9422467 U1                 | 03-07-2003          |
| EP 0197000                                | A | 08-10-1986          | CH | 666510 A5                  | 29-07-1988          |
|   |   |                     | AT | 49787 T                    | 15-02-1990          |
|   |   |                     | DE | 3668480 D1                 | 01-03-1990          |
|   |   |                     | DK | 99286 A ,B,                | 06-09-1986          |
|   |   |                     | EP | 0197000 A1                 | 08-10-1986          |